



The Rooflight Company

NS Plus



neo™ Rooflight (steel) By The Rooflight Company

Detailed description

Features:

- Mild steel sections, with a protective coating and polyester powder coated
- Edge-to-edge glazing.
- Top hung with electric actuation or with a discreet handle at the cill.
- Simple, clean lines.
- Plain linings for on site decoration.
- Can be linked together.
- An optional glazing bar is available for conservation applications.

Product guidance - As Standard

Size:

- Steel range: 15 portrait, landscape or square standard sizes.
- neo™-steel S10 and S13 are only available as a fixed shut option.

Frame material:

- Steel:

- Mild steel sections, with a protective polyester powder coating.
- Integral Thermoliner® PVC-U decoupled lining improves thermal performance and drains away any condensation.

Colour:

RAL 7022 Umber Grey.

Glazing details:

Standard: 4 mm SGG PLANITHERM® TOTAL + (Low E) toughened inner, 16 mm argon cavity, 4 mm SGG BIOCLEAR® (self clean only) toughened outer.

Warranty:

Rooflights must be registered online to receive the full warranty.

Options

Colour:

Any RAL or BS paint colour can be specified to match the roof tile.

Glazing details:

Enhanced glazing specification incorporating thermal, acoustic, security, light transmission, passive solar gain and decorative options available.

Blind:

- Pleated and roller blinds available in two fabric options and a range of colours.
- Rod and electric operation with pleated blind options available for use out of reach.

Product specification

Manufacturer

- Name: The Rooflight Company
- Web: www.therooflightcompany.co.uk
- Email: info@therooflightcompany.co.uk
- Tel: +44 (0)1993 833108
- Fax: +44 (0)1993 831066
- Address: Wychwood Business Centre, Milton Road, Shipton-under-Wychwood, Oxfordshire OX7 6XU

Product reference neo™ Rooflight (Steel)

Size (clear viewable sizes) neo™-S2 - 385 x 545 mm, Portrait. Steel.
neo™-S3 - 385 x 848 mm, Portrait. Steel.
neo™-S4 - 467 x 767 mm, Portrait. Steel.
neo™-S5 - 467 x 1162 mm, Portrait. Steel.
neo™-S6 - 537 x 848 mm, Portrait. Steel.
neo™-S7 - 622 x 962 mm, Portrait. Steel.
neo™-S8 - 622 x 1457 mm, Portrait. Steel.
neo™-S9 - 841 x 1153 mm, Portrait. Steel.
neo™-S10 - 947 x 1542 mm, Portrait. Steel.
neo™-S11 - 962 x 622 mm, Landscape. Steel.
neo™-S12 - 1457 x 622 mm, Landscape. Steel.
neo™-S13 - 1542 x 947 mm, Landscape. Steel.
neo™-S14 - 622 x 622, Square. Steel.
neo™-S15 - 947 x 947 mm, Square. Steel.

Frame colour Umber Grey (RAL 7022)
RAL ____
BS ____
As drawing ____
As schedule ____

Glazing details 4 mm SGG PLANITHERM® TOTAL + (Low E) toughened inner, 16 mm argon cavity, 4 mm SGG BIOCLEAN® (self clean only) toughened outer - Glass centre pane U Value:1.2 W/m²K.

Operation	Electric cill motor Manual handle Manual winder
Blind	[_____]
Type	Not required Dual Pleated Blind Roller Blind - Natural Plains Roller Blind - Blackout Single Pleated Blind
Operation	Electric - Pleated blinds only. Manual Rod
Type	Not required Dual Pleated Blind Roller Blind - Natural Plains Roller Blind - Blackout Single Pleated Blind
Operation	Electric - Pleated blinds only. Manual Rod