





ALL WORK ON OR WITHIN 3M OF BOUNDRY, TO BE WITH ADJ. OWNERS WRITTEN AGREEMENT, RE. PARTY WALL ACT 1996. ADJ. OWNERS TO BE GIVEN MIN. 2 MONTHS WRITTEN NOTICE OF COMMENCEMENT OF WORK.

NOTES MARKED THUS: ● NOT APPLICABLE



RAFTERS TIMBER GRADE C16

REVISION 'B' DATE 3-2-2016
RAFTER TIMBER GRADE REVISED AS PER ENGINEERS CALCULATIONS.

REVISION 'A' DATE 26-11-2015
EXTENSION REDUCED IN HEIGHT TO MAX. 4.0M ABOVE SITE LEVEL

- THIS DRAWING IS THE PROPERTY OF: JOHN HORTON WHO RETAINS THE SOLE COPYRIGHT OF ITS CONTENTS IN ENTIRETY, IT MAY NOT BE USED BY A THIRD PARTY WITHOUT PRIOR WRITTEN CONSENT.
- ALL MEASUREMENTS AND DRAIN RUNS TO BE CHECKED ON SITE BEFORE WORK COMMENCES.
- FOUNDATION DETAILS SUBJECT TO SITE EXCAVATION REVEALING LOADBEARING STRATA, UNSUITABLE STRATA WILL NECESSITATE AMENDED FOUNDATION DETAILS BEFORE WORK CONTINUES. ALL CONCRETE AND MORTAR BELOW D.P.C. IS TO COMPLY WITH B.R.E. DIGEST 250, CLASS 2 SULPHATES.
- FOUNDATIONS ON BOUNDARY OFFSET SO AS NOT TO ENCRUCH ON ADJOINING PROPERTY.
- FOUNDATIONS TAKEN DOWN BELOW DRAINS RUNNING UNDER PROPERTY, SHUTTER OUT AND PACK MIN. 50mm POLYSTYRENE AROUND DRAIN, R.C. LINTEL OVER DRAIN.
- OUTER WALLS CAVITY CONSTRUCTION: - 285mm CAVITY, 110mm BRICK, 85mm CAVITY INSULATED WITH ROCKWOOL CAVITY WALL BATTS, AGREEMENT NO. 79/686, 100mm THERMOLITE SHIELD, WALL TIES TO BE ST. STEEL, INNER FACE 12.5 PD, OR DABS, D.P.C. MIN. 150mm ABOVE G.L. WEAK MIX CONCRETE INFILL TO 225mm BELOW D.P.C., ALL CAVITIES CLOSED OFF AT TOP, NOT TO OBSTRUCT ROOF VENTILATION, WALL TIE C/C: - 450 VERTICAL, 750 HORIZONTAL, CAVITIES CLOSED WITH PATENT INSULATED D.P.C.
- INNER WALLS TO BE 100 X 50mm WOOD STOOTING, P.B. AND SKIM, PACKED WITH FIBREGLASS QUILT.
- INNER WALLS TO BE 100mm BLOCKWORK, 12mm PLASTER EACH SIDE, PROVIDE FOR D.P.C. MIN. 150mm ABOVE GROUND LEVEL.
- LINTELS TO BE I.G. L.I.V.S UNLESS OTHERWISE STATED, MIN. END BEARING 150mm EXTERNAL LINTELS TO BE INSULATED.
- ALL LINTELS AND STEEL BEAMS TO BE ENCASED WITH 18mm P.B. AND 7mm SKIM TO GIVE 1/2HR. FIRE RESISTANCE.
- DOORS AND WINDOWS TO HAVE VERTICAL AND HORIZONTAL D.P.C. AND TO BE DRAUGHT STRIPPED.
- MASTIC SEAL TO ALL NEW WOODWORK AND U.P.V.C. FITTINGS.
- WINDOWS TO BE DOUBLE GLAZED AND HAVE TRICKLE VENT. AT HIGH LEVEL MIN. 800sq.mm PER ROOM, OPENING LIGHTS WILL BE MIN. 1/20 FLOOR AREA, ANY GLAZING WITHIN 800mm OF FLOOR LEVEL AND WITHIN 1500mm OF FLOOR LEVEL TO DOORS AND SIDE PANELS TO BE TOUGHENED SAFETY GLASS TO BS: 6206 C 1981 J MIN. 16mm AIR GAP TO DOUBLE GLAZING, ALL GLAZING TO HAVE MIN. SOFT E COATING, TO HAVE MAX. U VALUE 1.6W/SQ.M, DOORS TO BE 1.8W/SQ.M.
- KITCHEN TO HAVE FAN TO PROVIDE 8000sq.mm BACKGROUND VENTILATION AND EXTRACT AIR NOT LESS THAN 90 LITRES/SEC. INTERMITTENT OPERATION, ALL HOT WATER PIPES TO BE INSULATED.
- SUSPENDED TIMBER FLOOR: - 18mm T4G WEYROCK BOARD (FLOORING GRADE 3) ON 150 X 50mm JOISTS AT 400mm C/C. WEYROCK IN HAZARDOUS AREAS TO BE GRADE II-III.
- OVERSITE: - 150mm CONCRETE ON 1200 GAUGE VISQUEEN D.P.M. ON 25mm COARSE SAND BLINDING ON 100mm CLEAN, WELL CONSOLIDATED HARDCORE, D.P.M. LAPPED INTO D.P.C.
- CONCRETE FLOOR: - 75mm SCREENED ON 500 GAUGE POLYTHENE SHEET ON 80 CELOTEX INSULATION BOARD ON 1200 GAUGE VISQUEEN D.P.M. ON 150mm CONCRETE ON 100mm CLEAN WELL CONSOLIDATED HARDCORE D.P.M. LAPPED INTO D.P.C.
- AIR BRICKS: - TIMBER FLOOR: - 220 X 150mm AIR BRICKS TRUNKED THROUGH CAVITY WITH D.P.C. OVER SUB-FLOOR VENTILATION MAINTAINED TO EXISTING TIMBER FLOOR THROUGH 220 X 150mm APERTURES THROUGH ORIGINAL OUTER WALL, MIN. 1500sq.mm/M RUN.
- AIR BRICKS: - CONCRETE FLOOR: - 220 X 150mm AIR BRICKS TRUNKED THROUGH CAVITY WITH D.P.C. OVER, THEN TRUNKED THROUGH INO. 100mm P.V.C. PIPE PER AIR BRICK THROUGH FLOOR TO VENTILATE EXISTING TIMBER FLOOR, MIN 1500sq.mm/M RUN.
- PITCHED ROOF: - MARLEY CAST CONC. TILES TO MATCH EXISTING ONTO 32 X 25mm BATTENS ON SARKING FELT ON 150 X 50mm RAFTERS AT 400 C/C, 25mm CEILING JOISTS AT 400 C/C, 25mm FIBREGLASS QUILT ONTO 500 GAUGE POLYTHENE VAPOUR BARRIER AND SKIM.
- FLAT ROOF: - COLD DECK CONSTRUCTION: - 3No. LAYERS BUILT UP ROOFING FELT, INO. LAYER GREEN MINERAL FELT 30g/m ON SINGLE PLY VENT LAYER HAVING 8mm DIA. HOLES AT 50mm C/C LAID FULLY BONDED ON 96 THERMOFOD KINGSPAN INSULATION BOARD LAID ON VAPOUR BARRIER, ONE LAYER OF BITUMINOUS FELT LAID POUR AND ROLL METHOD ON 18mm T 4 G WEYROCK BOARD 1 ROOFING GRADE 3 ON 30 KINGSPAN ON FIRTINGS TO GIVE TILT OF 1-40, ON X 50 JOISTS AT 400 C/C, 12.5 P.B. AND SKIM.
- ROOF INSULATION: - 120 FIBREGL. BETWEEN JOISTS, 150 FIBREGLASS QUILT COUNTER LAID ACROSS JOISTS.
- 30 X 3mm GALVANIZED STEEL LATERAL RESTRAINT STRAPS AT FIRST FLOOR AND ROOF LEVEL, STRAPS NAILED ACROSS MIN. 300 FLOOR JOISTS AND RAFTERS.
- ROOF TIED DOWN WITH 30 X 3mm MILD STEEL STRAPS ANCHORED TO WALL 450mm BELOW TOP COURSE AND MAXIMUM 2M C/C.
- ROOF TO HAVE 150mm FELT UPSTAND FLASHED TO BRICKWORK AND TUCKED IN, WITH CODE 4 LEAD COVER FLASHING OVER.
- TILT FILLETS TO ROOF.
- TILT ROOF TOWARDS 100mm HALF-ROUND P.V.C. GUTTER WITH 63mm P.V.C. R.W.P.
- ALL TIMBER JOIST ENDS TREATED WITH PRESERVATIVE WHERE BUILT IN.
- R.W.P. DISCHARGING ONTO ROOF: - FITTED WITH ANTI-SLASH BACK SHOE, DISCHARGING ONTO 450 X 450 X 8mm SLATE, SET IN HOT APPLIED BITUMEN.
- PATENT COLLAR TO ANY WASTE PIPES PASSING THROUGH ROOF.
- STEELWORK DETAILS: - DOUBLE BEAMS BOLTED TOGETHER AT MID. QUARTER POINTS WITH BARREL SPACERS, BEAMS TO BE GRADE 43 STEEL TO BS: 449 PAINTED WITH 2No. COATS RED OXIDE PRIMER.
- SUPPORT BRICK / BLOCKWORK TO BE OF CRUSHING STRENGTH 3.5N/mm MIN. WITH 1:1:6 CEMENT, LIME, SAND MORTAR C.P.11, PART 1, STRIPPED.
- UNDERGROUND DRAINS: - 100mm HEAVY DUTY P.V.C. DRAINS SURROUNDED IN 100mm PEA-GRAVEL, MIN. FALL 1 - 60. CONCRETE SLAB OVER TRENCH WHERE DRAIN PASSES UNDER BUILDING OR DRIVE.
- ALL INTERNAL WASTES TO BE FITTED WITH 75mm DEEP SEAL TRAPS, 38mm WASTE TO BATH AND SHOWER, 32mm TO W.H.B., 100mm TO W.C., 38mm WASTE TO SINK, ALL HOT WATER PIPES TO BE INSULATED.
- ALL WASTES TO BE U.P.V.C. AND TO HAVE RODDING EYE AT EACH CHANGE OF DIRECTION.
- BATHROOM TO HAVE FAN TO EXTRACT AIR NOT LESS THAN 15 LITRES/SEC. INTERMITTENT OPERATION, FAN TO HAVE 15MIN. RUN ON RELAY, EN-SUITE ALSO.
- LIGHTING TO BATHROOM AND EN-SUITE OPERATED BY PULL-CORD SWITCH.
- STAIR DETAIL: - CLEAR WIDTH: - 800mm RISE: - 200mm, MAX., 60 - MIN. 225 PITCH: - 42° MAX., HEADROOM: - 2M MIN. AT NOSING MIN. GOING TO TAPERED TREADS: - 50mm MAX. GAP TO VERTICAL BALUSTRADES: - 100mm HANDRAIL HEIGHT: - 900 - 1000mm
- SMOKE ALARMS INDICATED THUS: ● TO BE INTERLINKED AND SEPARATELY WIRED AND FUSED AT DISTRIBUTION BOARD IN ACCORDANCE WITH BS: 5466, AND FITTED WITH BATTERY BACKUP.
- DOOR MARKED THUS: * TO BE 1/2 HR. F.R. SELF-CLOSING WITH 32 X 25 SCREWED AND GLUED STOPS WITH INTUMESCENT STRIPS AND COLD SMOKE SEA S.
- ROOF: - MARLEY CAST CONC. TILES TO MATCH EXISTING ONTO 32 X 25mm TILING BATTENS, ON SARKING FELT ON TRUSSED RAFTERS AT 600 C/C. CALCS. TO BE SUPPLIED BY MANUFACTURER, DESIGNED TO BS: 5268: PART 3: 1985.
- CEILING: - 250mm FIBREGLASS QUILT ON 500 GAUGE POLYTHENE VAPOUR BARRIER, 12.5mm P.B. AND SKIM.
- LONGITUDINAL AND DIAGONAL WIND BRACING LAP-JOINTED AS NECESSARY, TO ABUT EACH GABLE WALL.
- COMPOUND HIP GIRDER TRUSSES SECURELY NAILED TOGETHER AT 400 C/C.
- HIP MONO TRUSSES TRIMMED TO HIP BOARD ON SITE.
- N.B. 200 X 38mm HIP BOARD TO EACH CORNER.
- SIMPSON STRONG-TIE JOIST HANGERS TYPE 46, 150mm UPSTAND TO CODE 4 LEAD FLASHING TUCKED INTO BRICKWORK WITH FLASHING TRAY OVER.

ITS HOME IMPROVEMENT TIME	CLIENT		
	MRS. C. BENTHAM		
	ADDRESS		
	33 HOWBRAY VILLAS SOUTH SHIELDS NE33 3GA		
	JOB TITLE		
	PROPOSED SINGLE STOREY REAR EXTENSION		
PLANS DRAWN FOR YOUR HOME EXTENSION	DRAWING TITLE		
TEL. JOHN HORTON 0191-454 3870 MOBILE 07435 969 151	CONSTRUCTION DETAILS		
	DATE	SCALE	DRAWING NUMBER
	10-11-2015	1:50	2015-142
			SHEET 3 OF 3 SHEETS
			REVISION 'B'

STO 161 / 16 NMA